



Water Regulations Approved Products

Note: Browsers which use the Adobe Acrobat plugin (e.g. Mozilla Firefox) will not display digital signatures. For the correct display please open the certificate directly in Adobe Acrobat Reader.

Products Testing Requirements



2308783

 Search

Want to be able to come straight back to these results?
Click the Results button to get a link directly to this page

1 matching product found

2308783

Section Code 2185 Valves

Non-return, spring loaded, resilient trim.

Reassessment Due August 2028

RIRN N/A.

Manufacturer Steve Leigh & Associates Ltd.

Factor

Model NRV2 Check Valve Assembly Lo-Flo – Fixed Flow Rate 12 litres/min (red)

NRV2 Check Valve Assembly Lo-Flo – Fixed Flow Rate 14 litres/min (pink)

NRV2 Check Valve Assembly Lo-Flo – Fixed Flow Rate 10 litres/min (light blue)

Size Nominal Diameter 20mm – DN20.

Marking NRV on body.

Description Range of non-return valves with plastic bodies.

ATS3 – Without Production Surveillance.

Scope Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature: Cold Water Use Only.

Hygienic Purposes: Non-metallic materials suitable for continuous use with cold water only.

Materials Non-metallic materials assessed (BS6920) to point of discharge.

Backflow N/A.

Protection

Additional Notes All water contact & exposed components satisfy opacity requirements.