

PIPE INSTALLATION

OPTIONS FOR THE INSTALLATION OF Groundbreaker®

OPTION 1

Universal
key

Impermeable
membrane
seals wall
gaps

Toggle
Latch

Easy access to
control valve
and water meter
(if required)

Seal
compliant with
Building Regulations
Approved Document
Part L1A

INSUduct

Standard
25mm Ø MDPE pipe
adaptor available for
32mm Ø MDPE or
copper

Groundbreaker® is fully compatible
with these pipe connections:

CONNECTION
DETAIL

Universal
Pipe
Connection




PROTECTA-LINE
Pipe Systems

OPTION 1

THROUGH WALL

As supplied: Use 90° pre-formed bend (supplied) from Groundbreaker® to take the water supply through the wall and plumb as normal.

To use the universal pipe insert, it will be necessary to remove 40mm from the upstand end of the pre-formed PE pipe, or revert to a standard PE pipe insert (not supplied).



Use SHallduct™ to insulate
All installations may need to
be approved / certified by
local water company.

For other pipe sizes entering
Groundbreaker®, please use
Philmac Connections as available
through your local stockists.

Failure to install Groundbreaker to this specification will eliminate the manufacturers guarantee and may result in a water company refusing to connect the water service

To view installation video - visit www.groundbreaker.co.uk